



UNIVERSIDADE FEDERAL DE JATAI
CNPJ:35.840.659/0001-30
QUADRA AREA LOTE AREA KM 192
Rodovia BR-364 3800, KM 192
Setor Francisco Antonio
JATAI - GO
75801-615
BRASIL

Carl Zeiss do Brazil Ltda.
Rod Antonio Heil 1001 KM01
Armz G11 Itajaí,SC
88316-001

Contato Comercial

Nome: Jean Barboza

Contato do cliente

Nome:
Telefone:
Fax:
E-mail:

Data: 29/05/2026
Página: 1 de 2

Proposta

Proposta Nº: 7761581319
Cliente Nº: 2120024

Item	ID do produto / Descrição do Produto	Quant.	Preço unitário (BRL)	Preço Total (BRL)
10	491905-9880-010 Stereo Microscope Stemi 355 Stereo Microscope Stemi 355 Consisting of the following items:	1 PC		
20	435066-9520-000 Microscope Set Stemi 355 Edu Microscope Set Stemi 355 Edu Microscope Body Stemi 355 - Greenough system - Manually operable zoom 5.5:1 (0.72x. 4.0x) on both sides - Fixed zoom clickstops 0.72x-1x-2x-3x-4x - Free working distance 110 mm - Viewing angle 45° with adjustable interocular distance 55. 75 mm - Eyepiece mount 30 mm with maximum field number 23 mm - Mount D=76 mm for Stemi mount/Mount S - Interface D=66 mm for illuminators - Thread M52 for front optics or analyzer - Integrated near-vertical LED illumination (IVI)for stands C Edu/Lab/Mat, stand L LED, Controller C Additionally included: - Eyepieces 10x/23 Br. foc. - Spiral cable with left latch offset RJ12	1 PC		



Stand C Edu

- Stand base D331xW204xH35 mm
 - Working surface D209xW160 mm
 - Interfaces d=84 mm for stages and d=46 mm for TL polarizer
 - Column 303 mm with drive and handle, lifting range 145 mm
 - Stemi mount d=76 mm, load capacity 7 Kg, adjustable friction
 - 2x sockets for IVI and illuminator C LED
 - Separate RL/TL controls for on/off/dimming
 - ECO button
 - 2x USB-C sockets for power input and output
 - Built-in LED transillumination brightfield/darkfield, switchable
 - Integrated power unit 12V DC 24W/100...240V AC/50...60Hz
- Additionally included:
- Glass and B/W plastic plate D=84x5 mm
 - Dust cover

Spot Illuminator C LED

- Single spot for brightfield and darkfield epi-illumination
- Thread M24x0.5 for polarizer
- Height adjustable, inclinable, zoomable
- For stands C Edu/Lab/Mat and stand L LED

30	444802-9000-000	2 PC
----	-----------------	------

Eyecup w/light protection foldable

Eyecup with light protection foldable

- to minimize disturbing light incidence
- foldable, usable with eyeglasses

40	435528-9010-000	1 PC
----	-----------------	------

Double Spot illuminator C LED

Double Spot Illuminator C LED

- Gooseneck double spot, 2x 160 mm for variable epi-illumination
- 2x thread M24x0.5 for polarizer
- Height adjustable
- For stands C Edu/Lab/Mat and stand L LED

Subtotal POR UNIDADE	18.447,09 BRL
TOTAL	18.447,09 BRL

Em conformidade com as normas aplicáveis, relacionadas com as disposições europeias e dos Estados Unidos da América sobre o controlo das exportações, a presente proposta apenas terá validade em caso de que não haja nenhuma proibição de venda, e, se a venda estiver sujeita a licenças oficiais, se estas tiverem sido obtidas. Se o acordo não entrar em vigor devido a normas aplicáveis sobre o controlo de exportações, a presente proposta fica sem efeito, e fica excluída qualquer reclamação ou responsabilidade, em especial por danos, contra a ZEISS.